



# OWNER'S MANUAL

## QUICK STROP

### #214

#### **WARNINGS & CAUTIONS**

1. Only appropriately trained rescue personnel shall use the Quick Strop.
2. The Quick Strop shall be used to hoist **uninjured** persons only.
3. The crotch (safety) strap shall be connected and adjusted during each lift.
4. Inspect all materials, webbing, and hardware for proper condition prior to use.
5. Ensure that the crotch strap is properly stowed prior to use.

#### **DESCRIPTION**

Originally designed for the US Coast Guard, the LSC Quick Strop is constructed of MIL-SPEC webbing and stainless steel hardware, the Quick Strop provides a quick, safe means of hoisting **uninjured** personnel. The Strop is designed to be secured under the arms of the survivor in one quick motion. To prevent the survivor from slipping out, a friction keeper slides down the Strop and attaches to an adjustable crotch safety strap, stored in a zipper pocket on the rear of the Strop. Instructions and pictorials are printed on the Strop.

#### **USING YOUR QUICK STROP**

1. The Strop can be placed over-the-head and positioned around the back and under the arms. If the survivor needs to maintain a grip, rescuers can remove the red-banded strap from the hook to wrap around the survivor and reattach through the friction keeper.
2. If v-ring is removed, reinsert through slide buckle, pull slide buckle down both webbing legs to snug Strop around upper chest (under arms), with adjuster positioned in front of chest.
3. Remove crotch strap from pocket, pass between the legs and clip hook onto the friction keeper.
4. Adjust as required, leaving slightly loose as strap will pull up during hoisting.
5. Keep arms down and folded across chest. See pictorial on inside of Strop.
6. Do not fold the padded area of the Strop.

#### **INSPECTION**

1. Inspect all materials, webbing, and hardware for cuts, abrasions, cracks, deterioration, and excess wear.
2. Remove from service any Strop with damage.
3. Every 6 months, apply a 600 lb. load to the extended Strop (v-ring to v-ring).

#### **MAINTENANCE**

1. Rinse thoroughly with fresh water, and air-dry the Strop after salt-water exposure.
2. Check the crotch strap adjuster and snap hooks for proper operation. Accordion fold and re-stow; ensure that the hook & loop closure matches properly on the crotch strap storage pocket and the crotch strap.
3. Mild soap and water can be used to hand wash the Strop.

#### **WARRANTY**

LSC products are warranted to the first consumer purchaser to be free from defects in material or workmanship for a period of twelve (12) months. Please contact LSC for our complete Warranty information and Policies, or visit our website.

#### **LIFESAVING SYSTEMS CORP.**

220 ELSBERRY RD.  
APOLLO BEACH, FL 33572  
PHONE: 813/645-2748  
quality@lifesavingsystems.com  
www.lifesavingsystems.com