



# OWNER'S MANUAL JSDF TETHER #467-JSDF

## WARNING

The product(s) covered by this manual is (are) of a rescue and survival equipment nature. Inherent to all rescue and survival environments is an increased risk of injury and/or possible death to an individual or group of individuals. This equipment is intended to aid the professional rescuer(s) and/or survival victim(s). However, all risks for injury or death cannot be completely eliminated or foreseen. Equipment training, including continued proficiency reviews and maintenance, is vital to the proper and safe use of all rescue and survival type equipment. It is the responsibility of the purchasing and end-user organization or individual to define the operational procedures and safety guidelines associated with the proper utilization, maintenance (including service life) and storage of the rescue and survival equipment. All individuals must be thoroughly trained and familiarized with the intended purpose, correct use and function of the equipment. Failure to do so may result in serious injury or death.

## INSTRUCTIONS

Secure tether to approved load-bearing hardware/device suitable for the intended application. Always keep tether adjusted to minimize slack/length at all times. Use the elastic loops to retain free end of tether strap.

Recommended Working Load Limit (WLL) not to exceed one (1) person or 600 lbs.

## USER INSPECTION

Periodic inspections are necessary to ensure functional reliability. Prior to and after each use, inspect the entire tether assembly for cuts, broken stitches or unusual wear. Check the adjuster and attached carabineers or hardware for correct operation. Remove tether from service immediately if any discrepancy is identified.

## MAINTENANCE INSPECTION

If unit has excessive soiling, or after direct exposure to salt water, salt spray, fuel, oils or other chemicals clean the entire tether with fresh water and mild detergent. Thoroughly rinse and allow to completely air dry, away from direct exposure to sunlight.

Service Life: Pending passing of inspections, but not to exceed 10 years from date of manufacture (DOM).

## WARRANTY

LSC products are warranted to the first consumer purchaser to be free from defects in material or workmanship for a period of twelve (12) months. Please contact LSC for our complete Warranty information and Policies, or visit our website.

## LIFESAVING SYSTEMS CORP.

220 ELSBERRY RD.

APOLLO BEACH, FL 33572

PHONE: 813/645-2748

FAX: 813/645-2768

[www.lifesavingsystems.com](http://www.lifesavingsystems.com)

*Lifesaving Systems Corp.*

*#F-750-467-JSDF OM (Rev A) Updated 2011-10-10*



# OWNER'S MANUAL JSDF TETHER #467-JSDF

## WARNING

The product(s) covered by this manual is (are) of a rescue and survival equipment nature. Inherent to all rescue and survival environments is an increased risk of injury and/or possible death to an individual or group of individuals. This equipment is intended to aid the professional rescuer(s) and/or survival victim(s). However, all risks for injury or death cannot be completely eliminated or foreseen. Equipment training, including continued proficiency reviews and maintenance, is vital to the proper and safe use of all rescue and survival type equipment. It is the responsibility of the purchasing and end-user organization or individual to define the operational procedures and safety guidelines associated with the proper utilization, maintenance (including service life) and storage of the rescue and survival equipment. All individuals must be thoroughly trained and familiarized with the intended purpose, correct use and function of the equipment. Failure to do so may result in serious injury or death.

## INSTRUCTIONS

Secure tether to approved load-bearing hardware/device suitable for the intended application. Always keep tether adjusted to minimize slack/length at all times. Use the elastic loops to retain free end of tether strap.

Recommended Working Load Limit (WLL) not to exceed one (1) person or 600 lbs.

## USER INSPECTION

Periodic inspections are necessary to ensure functional reliability. Prior to and after each use, inspect the entire tether assembly for cuts, broken stitches or unusual wear. Check the adjuster and attached carabineers or hardware for correct operation. Remove tether from service immediately if any discrepancy is identified.

## MAINTENANCE INSPECTION

If unit has excessive soiling, or after direct exposure to salt water, salt spray, fuel, oils or other chemicals clean the entire tether with fresh water and mild detergent. Thoroughly rinse and allow to completely air dry, away from direct exposure to sunlight.

Service Life: Pending passing of inspections, but not to exceed 10 years from date of manufacture (DOM).

## WARRANTY

LSC products are warranted to the first consumer purchaser to be free from defects in material or workmanship for a period of twelve (12) months. Please contact LSC for our complete Warranty information and Policies, or visit our website.

## LIFESAVING SYSTEMS CORP.

220 ELSBERRY RD.

APOLLO BEACH, FL 33572

PHONE: 813/645-2748

FAX: 813/645-2768

[www.lifesavingsystems.com](http://www.lifesavingsystems.com)

*Lifesaving Systems Corp.*

*#F-750-467-JSDF OM (Rev A) Updated 2011-10-10*