#190-A Litter Hoisting Sling

Horizontal hoisting sling designed for quick connect and disconnect to Medevac and Stokes-type litters. All components, including the 5/32" cable, are corrosion resistant stainless steel. Snap hooks are marked with color-coded reflective tape; additional tape is provided for marking the litter frame.

Approved for US Navy (NAVAIR) and US Coast Guard use.

Technical Specifications:

#190-A Hoist Sling		
Breaking Strength:	O-Ring:	5,000lbs (2,268kg)
	Locking Snap Hook:	4,500lbs (2,041kg)
	Cable:	2,400lbs (1,089kg)
Dimensions:	Long Cables: 41″ (104.14cm)	
	Short Cables: 33" (83.82cm)	
Material:	Major Components, Stainless Steel	
Weight:	~3.0lbs (1.36kg)	
Working Load Limit (WLL):	600lbs (272kg)	
Load Strength:	Exceeds 2500lb Mil-Spec litter load requirement	
Service Life:	Based on usage and condition, recommend replacement after 10 years	
NSN	1670-01-226-5300	

Features:



Corrosion Resistant Stainless Steel

LIFESAVING SYSTEMS CORPORATION

② 220 Elsberry Road, Apollo Beach, Florida 335<u>72</u>



(813)645-2748







