

# #214 Quick Strop

Constructed of MIL-SPEC webbing and stainless steel hardware, the strop provides a quick, safe means of hoisting uninjured personnel. Designed to be placed under the arms and around the back. Rescue personnel can slide the Strop over the head of the survivor and into place in a single quick motion. To prevent the survivor from slipping out, a friction buckle is slid down the Strop and attached to an adjustable safety strap (stowed in rear zipper pocket). Instructions and pictorials are printed on the Strop.



## Technical Specifications:

#214 Quick Strop	
Weight:	2.54lbs (1.15kg)
Color:	International Orange Cover with Black Webbing
Fabric Cover:	420 Denier Nylon
Webbing Breaking Limit:	Load Bearing: Type 10 MIL-Spec Nylon Webbing- 10,000lbs (4,535kg)
	Crotch Strap: Type 13 MIL-Spec Nylon Webbing- 7,000lbs (3,175kg)
Static Load Test:	Meets 3,372lbf (15kN) for 3 minutes per ATSO-C1003 requirement
Hardware:	V-Ring (Stainless Steel) Working Load Limit – 5,000lbs (2,268kg)
	Snap Hook (Stainless Steel) Breaking Limit – 2,650lbs (1,202kg)
Working Load Limit (WLL):	600lbs (272kg)
Service Life:	12 years from date placed in service when inspected in accordance with maintenance instructions.
NSN:	4240-01-545-6722

LIFESAVING SYSTEMS CORPORATION

220 Elsberry Road, Apollo Beach, Florida 33572

(813)645-2748

www.lifesavingsystems.com

