

#214-SAP Quick Strop

Similar to the #214 the modified quick strop provides more support in the seat and has a sling with seat straps that distribute weight more evenly for more comfort and less compression of the chest than the conventional strop. It also utilizes a single V-Ring for attachment to the hoist hook. A secondary safety hook is installed near the hook attachment V-Ring. This design allows the quick strop to be used without opening the gate of the helicopter hoist hook during the rescue.



Technical Specifications:

#214-SAP Quick Strop	
Weight:	3.70lbs (1.68kg)
Color:	International Orange Cover with Black Webbing
Fabric Cover:	420 Denier Nylon
Webbing Breaking Limit:	Load Bearing: Type 10 MIL-Spec Nylon Webbing- 10,000lbs (4,535kg) Crotch Strap: Type 8 MIL-Spec Nylon Webbing- 4,000lbs (1,814kg)
Static Load Test:	Meets 3,372lbf (15kN) for 3 minutes per ATSO-C1003 requirement
Hardware:	V-Ring (Stainless Steel) Working Load Limit - 5,000lbs (2,268kg) Snap Hook (Stainless Steel) Breaking Limit - 2,650lbs (1,202kg) Talon II Hook (Titanium) Working Load Limit - 5,000lbs (2,268kg)
Working Load Limit (WLL):	600lbs (272kg)
Service Life:	10 years from date placed in service when inspected in accordance with maintenance instructions.

LIFESAVING SYSTEMS CORPORATION

220 Elsberry Road, Apollo Beach, Florida 33572

(813)645-2748

www.lifesavingsystems.com

