

# #410-AF D-LOK Hoist Hook

The D-LOK incorporates an automatic dual-lock latch gate design for ultimate safety. The double lock gate provides security to prevent accidental openings, while allowing the latch gate to be operated quickly and easily with one hand. The hoist hook features a large ring volume for multiple equipment rings, and will accept rings over one inch in diameter. Integral utility eye allows attachment of tag/guide line. Hook is constructed entirely of stainless steel for strength and corrosion resistance.

The D-LOK Hoist Hook eliminates all problems associated with the current double rescue hook, such as inadvertent engagement (including the snagging of fingers on the small hook), and self-release (ring roll-out). The LSC D-LOK Hoist Hook exceeds the load test requirement for the double rescue hook (MS-18027-2A), and is available with seven (7) attachment options to fit all current hoist installations.



Authorized for U.S. Army H-60  
Aircraft in AWR-980 R17

## Fitment Configuration:

Thread Size	End Configuration /Attachment	Overall Shaft Length (Inches)	LSC Part Number
.500-20 UNJF-3A	Slot and Pin Hole	1.000"	410-AF

## Technical Specifications:

#410-AF D-LOK Hoist Hook	
Weight:	~1.5lbs (0.68kg)
Proof Load:	3,000lbs (1,360kg)
Hook Body:	Forged Stainless Steel
Breaking Limit:	7,000lbs (3,175kg)
Working Load Limit (WLL):	600lbs (272kg)
Maintenance:	Regular lubrication with a light machine oil
Cleaning:	Fresh water rinse after exposure to saltwater environment

LIFESAVING SYSTEMS CORPORATION



220 Elsberry Road, Apollo  
Beach, Florida 33572



(813)645-2748



www.lifesavingsystems.com

