

Rescue Line

498-F



Polypropylene Rope, 3/8" Hollow-braid, monofilament construction provides good handling characteristics, positive flotation, and can be easily spliced. Breaking strength 2,200 lbs.
Sold by the foot or 1,000' roll.

500-F



Max-Grip Safety Line, 3/8" A Hollow-braid MFP jacket in high visibility golden-yellow surrounds a multifilament polypropylene core. Line has positive flotation and excellent flexibility characteristics. Jacket is a unique braid of alternating strand diameters forming a tread-like pattern for improved hand grip in wet conditions. Breaking Strength 1,800 lbs.
Sold by the foot or 1,000' roll.

503-F



Water Rescue Rope, 7/16" (Professional) Redesigned with a larger diameter for improved handling and grip. Multifilament polypropylene sheath of 16-strand kernmantle construction provides abrasion and UV protection for the multifilament polypropylene core. Sheath is high-visibility yellow with red tracers. Excellent flotation characteristics. Breaking Strength 2,500 lbs.
Sold by the foot or 1,250' roll.

Technical Specifications:

Part Number	Breaking Strength	Weight
498-F	2,200lbs	2oz per foot (57g), 17.5lbs (8kg) per 1,000' roll.
500-F	1,800lbs	5oz per foot (142g), 50lbs (23kg) per 1,000' roll.
503-F	2,500lbs	5oz per foot (142g), 62.5lbs (28kg) per 1,250' roll.

LIFESAVING SYSTEMS CORPORATION

 220 Elsberry Road, Apollo Beach, Florida 33572

 (813)645-2748

 www.lifesavingsystems.com

