Lifesaving Systems Corp.
220 Elsberry Road • Apollo Beach, FL 33572
Phone 813/645-2748 • FAX 813/645-2768
www.lifesavingsystems.com • E-mail: info@lifesavingsystems.com

Product Specification
LSC Style #500
3/8” Safety Rope, Grip-Line

Core:	High-tenacity multifilament polypropylene.
Sheath:	High-tenacity multifilament polypropylene braided sheath with alternating strand diameters for improved grip. Individual strands to have small twist for improved abrasion and pick resistance.
Float:	Rope to have excellent flotation characteristics with specific gravity of 0.95 or less.
UV:	High UV resistance. Fibers to have UV inhibitors.
Flexibility:	Rope should possess good hand/feel and allow for easy fold/stuffing into rope bags.
Tensile:	Breaking strength of 1800lbs (816kg).
Diameter:	3/8" (9.5 mm +0.50mm / -0.00mm).
Color:	Sheath - Bright Golden Yellow Core - White, Natural or Yellow.
Put-up:	1000 ft/spool (+3%, 0%), no breaks (continuous).

Certification

This is to certify that the above indicated material has been tested and conforms to the requirements of Lifesaving Systems Corp #500 Max-Grip Safety Line, 3/8”.

Kevin Lehoe 1/8/2018
Quality Manager