

#216 Rescue Strop

The Rescue Strop is designed to be unaffected by repeated use in the marine environment; constructed of nylon, closed-cell foam and stainless-steel hardware. The Strop is placed under the arms and across the back to hoist **uninjured** personnel during helicopter operations. The Survivor's arms must remain down to prevent slipping free of the Rescue Strop during hoisting. A safety strap is provided to secure the Survivor's arms down and by their sides. **ONLY** properly trained **MILITARY** personnel can use this item. This item **SHALL NOT** be used as a single Survivor strop on Civilians; **ONLY** as part of a **Double-Lift** by a trained **Military** rescuer.

The United States Army has approved this device per the Airworthiness Release (AWR) for Rescue Hoist Equipment on UH/HH-60 Helicopters (AWR 980).



#216 Rescue Strop	
Weight:	2.90lbs (1.32kg)
Color:	International Orange Cover with Black Webbing
Fabric Cover:	420 Denier Nylon
Webbing Breaking Limit:	Load Bearing: Type 10 MIL-Spec Nylon Webbing- 10,000lbs (4,535kg)
Hardware:	V-Ring (Stainless Steel) Working Load Limit – 5,000lbs (2,268kg)
	Snap Hook (Stainless Steel) Breaking Limit – 2,650lbs (1,202kg)
Working Load Limit (WLL):	600lbs (272kg)
Service Life:	15 years from date of manufacture or 12 years from date placed in-service when inspected in accordance with maintenance instructions.
NSN:	1680-01-347-4946

